

TOTAL STATION

RCS



TELESCOPIC

Length	154mm
Diameter	Telescopic: 45mm; EMD: 50mm
Magnification	30x
Image	Erect
Field of View	1°30'
Resolving Power	3"
Minimum Focus	1.5m

DISTANCE

Single Prism Range	5,000m
Accuracy	±(2mm+2mm*D)m.s.e
Non-prism Range	1,000m
Accuracy	±(3mm+2mm*D)m.s.e
Measuring Time	Fine: 0.3s; Normal: 0.2s
Meteorologic Correction	ATMOSense Auto Correction
Prism Constant	Manual

ANGLE

Accuracy	2"
Method	Absolute Encoding
Detecting System	H: dual; V: dual
Minimum Reading	1"/5"/10"
Diameter of Circle	79mm
Vertical Angle 0°	Zenith: 0°; Horizontal: 0°
Unit	360°/400gon/6400mil

DISPLAY

Display Unit	Graphic, 640*320 color touch LCD
No. of Displays	2
Keyboard	Alphanumeric

PLUMMET

Type	Ultra Plumb: Laser plummet with distancing function to measure instrument height.
Measuring Range	0.6-2.0m
Minimum Reading	1mm
Distance Accuracy	±3mm
Deviation	0.4mm @ 1.5m height
Spot Diameter	1.5mm @1.5m height

TILT CORRECTION

Tilt Sensor	Dual axis
Method	Liquid electric
Range	6'
Resolution	1"

LEVEL

Plate Level	30"/2mm
Circular Level	8'/2mm

DATA INTERFACE

Internal Memory	16,000 points
Data Interface	USB2.0
Wireless *	Bluetooth 2.1

GENERAL

Guide Light	Yes
Quick-meas Button	Yes
Weight	5.4kg
Dimension	353 (H) * 206 (L): 200 (W) mm
Operating Temperature	-20°C to 50°C
Battery	Li-on battery, 7.4V, 3000mAh
Water & Dust Proof	IP65
Working Duration	12h

* Not available on RCS Lite.

ITEM LIST

- Carrying case *1
- Total station *1
- Battery *2
- Charger & adapter *1
- Reflecting sheet *1
- Safety Vest *1
- Quick Guide *1
- Warranty Card *1



7F, Sicheng Road, Guangzhou 510663, China
www.ruide.xyz
support@ruideinstrument.com

[ruideinstrument](#)
[RUIDEPositioning](#)