

# TOTAL STATION

RNS



Android 6.0  
Marshmallow

## SYSTEM

OS	Android 6.0
Processor	MT6753, 1.5GHz, 8 cores
Internal Memory	RAM 3GB, ROM 32GB

## TELESCOPIC

Length	154mm
Diameter	Telescopic: 45mm; EMD: 50mm
Magnification	30x
Image	Erect
Field of View	1°30'
Resolving Power	3"
Minimum Focus	1.2m
Recticle	Illuminable 4 grades

## DISTANCE

Single Prism Range	5,000m
Accuracy	±(2mm+2mm*D)m.s.e
Non-prism Range	1,500m
Accuracy	±(3mm+2mm*D)m.s.e
Measuring Time	Fine: 0.3s; Normal: 0.2s
PPM Correction	Manual
Prism Constant	Manual

## ANGLE

Accuracy	2"
Method	Absolute Encoding
Detecting System	H: dual; V: dual
Minimum Reading	1"/5"/10"
Diameter of Circle	79mm
Vertical Angle 0°	Zenith: 0°; Horizontal: 0°
Unit	360°/400gon/6400mil

## DISPLAY

Display Unit	TFT LCD, 720*1280
No. of Displays	2
Keyboard	Numeric

## PLUMMET

Type	Laser
Deviation	1.5mm @ 1.5m height
Wavelength	630-670nm
Laser Class	Class II / IEC60825-1
Laser Power	<0.4mW

## COMPENSATOR

Tilt Sensor	Dual axis
Method	Liquid electric
Range	4'
Resolution	1"

## LEVEL

Plate Level	30"/2mm
Circular Level	8'/2mm

## COMMUNICATION

I/O Interfaces	RS232 Micro SIM USB Type-C (OTG) MicroSD
Bluetooth	Bluetooth 4.0
WLAN	Dual-band 8.2.11/a/b/g/n
Microphone/Speaker	Yes

## GENERAL

Quick-meas Button	Yes
Weight	5.7kg
Dimension	350 (H) * 200 (L): 710 (W) mm
Operating Temperature	-20°C to 50°C
Battery	Li-on battery, 7.4V, 3100mAh
Water & Dust Proof	IP55
Working Duration	8h

## ITEM LIST

Carrying case *1	Tool kit *1
Total station *1	Reflecting sheet *1
Battery *2	Plumb *1
MicroSD card *1	Rain cover *1
Type-C to USB OTG cable *1	Safety Vest *1
Type-C data cable *1	Quick Guide *1
Charger & adapter *1	Warranty Card *1



7F, Sicheng Road, Guangzhou 510663, China  
[www.ruide.xyz](http://www.ruide.xyz)  
[support@ruideinstrument.com](mailto:support@ruideinstrument.com)

[ruideinstrument](#)  
[RUIDEPositioning](#)